

# CIS macOS Safari Benchmark

v2.0.0 - 11-28-2017

# Terms of Use

This work is licensed under a Creative Commons Attribution-NonCommercial-ShareAlike 4.0 International Public License. The link to the license terms can be found at <https://creativecommons.org/licenses/by-nc-sa/4.0/legalcode>

To further clarify the Creative Commons license related to CIS Benchmark content, you are authorized to copy and redistribute the content for use by you, within your organization and outside your organization for non-commercial purposes only, provided that (i) appropriate credit is given to CIS, (ii) a link to the license is provided. Additionally, if you remix, transform or build upon the CIS Benchmark(s), you may only distribute the modified materials if they are subject to the same license terms as the original Benchmark license and your derivative will no longer be a CIS Benchmark. Commercial use of CIS Benchmarks is subject to the prior approval of the Center for Internet Security.

## Table of Contents

Terms of Use .....	1
Overview .....	4
Intended Audience.....	4
Consensus Guidance.....	4
Typographical Conventions .....	5
Scoring Information .....	5
Profile Definitions .....	6
Acknowledgements .....	7
Recommendations.....	8
1 General.....	8
1.1 (L1) Ensure 'Open "safe" files after downloading' is 'Disabled' (Scored) .....	8
2 Tabs.....	10
3 AutoFill .....	11
3.1 (L2) Ensure 'AutoFill web forms: User names and passwords' is 'Disabled' (Scored) .....	11
3.2 (L2) Ensure 'AutoFill web forms: Credit cards' is 'Disabled' (Scored).....	13
3.3 (L2) Ensure 'AutoFill web forms: Other forms' is 'Disabled' (Scored).....	15
4 Passwords.....	17
4.1 (L2) Ensure 'AutoFill user names and passwords' is 'Disabled' (Scored).....	17
5 Search.....	19
6 Security.....	20
6.1 (L1) Ensure 'Warn when visiting a fraudulent website' is 'Enabled' (Scored) ....	20
6.2 (L2) Ensure 'Enable JavaScript' is 'Disabled' (Scored) .....	22
6.3 (L2) Ensure 'Block pop-up windows' is 'Enabled' (Scored) .....	24
7 Privacy .....	26
7.1 (L1) Ensure 'Cookies and website data' is set to 'Allow from websites I visit' (Scored) .....	26
8 Websites.....	28
9 Extensions .....	28
10 Advanced.....	29

10.1 (L1) Ensure 'Show full website address' is 'Enabled' (Scored) .....	29
11 Other .....	31
11.1 (L1) Ensure 'Show Status Bar' is not 'Hidden' (Scored) .....	31
Appendix: Summary Table .....	33
Appendix: Change History .....	34

# Overview

This document, provides prescriptive guidance for establishing a secure configuration posture for Apple Safari 11.0.1 running on macOS Sierra. This benchmark was tested using Safari 11.0.1 on macOS 10.12.6. To obtain the latest version of this guide, please visit <http://cisecurity.org>. If you have questions, comments, or have identified ways to improve this guide, please write us at [support@cisecurity.org](mailto:support@cisecurity.org).

## Intended Audience

This document is intended for system and application administrators, security specialists, auditors, help desk, and platform deployment personnel who plan to develop, deploy, assess, or secure solutions that incorporate Apple's Safari Browser.

## Consensus Guidance

This benchmark was created using a consensus review process comprised of subject matter experts. Consensus participants provide perspective from a diverse set of backgrounds including consulting, software development, audit and compliance, security research, operations, government, and legal.

Each CIS benchmark undergoes two phases of consensus review. The first phase occurs during initial benchmark development. During this phase, subject matter experts convene to discuss, create, and test working drafts of the benchmark. This discussion occurs until consensus has been reached on benchmark recommendations. The second phase begins after the benchmark has been published. During this phase, all feedback provided by the Internet community is reviewed by the consensus team for incorporation in the benchmark. If you are interested in participating in the consensus process, please visit <https://workbench.cisecurity.org/>.

## Typographical Conventions

The following typographical conventions are used throughout this guide:

Convention	Meaning
<code>Stylized Monospace font</code>	Used for blocks of code, command, and script examples. Text should be interpreted exactly as presented.
Monospace font	Used for inline code, commands, or examples. Text should be interpreted exactly as presented.
< <i>italic font in brackets</i> >	Italic texts set in angle brackets denote a variable requiring substitution for a real value.
<i>Italic font</i>	Used to denote the title of a book, article, or other publication.
<b>Note</b>	Additional information or caveats

## Scoring Information

A scoring status indicates whether compliance with the given recommendation impacts the assessed target's benchmark score. The following scoring statuses are used in this benchmark:

### Scored

Failure to comply with "Scored" recommendations will decrease the final benchmark score. Compliance with "Scored" recommendations will increase the final benchmark score.

### Not Scored

Failure to comply with "Not Scored" recommendations will not decrease the final benchmark score. Compliance with "Not Scored" recommendations will not increase the final benchmark score.

## Profile Definitions

The following configuration profiles are defined by this Benchmark:

- **Level 1**

Items in this profile intend to:

- be practical and prudent;
- provide a clear security benefit; and
- not inhibit the utility of the technology beyond acceptable means.

- **Level 2**

This profile extends the "Level 1" profile. Items in this profile exhibit one or more of the following characteristics:

- are intended for environments or use cases where security is paramount
- acts as defense in depth measure
- may negatively inhibit the utility or performance of the technology

## Acknowledgements

This benchmark exemplifies the great things a community of users, vendors, and subject matter experts can accomplish through consensus collaboration. The CIS community thanks the entire consensus team with special recognition to the following individuals who contributed greatly to the creation of this guide:

### **Editor**

Paul Campbell, Anitian

Jordan Rakoske GSEC, GCWN



# Recommendations

## 1 General

This section contains settings under the general tab of the Safari Browser.

### 1.1 (L1) Ensure 'Open "safe" files after downloading' is 'Disabled' (Scored)

#### Profile Applicability:

- Level 1

#### Description:

The Safari browser contains a feature which causes all files considered "safe" to be automatically opened once they have finished downloading.

#### Rationale:

This feature is meant to be a benefit but having the browser automatically open files that could be malicious and downloaded by mistake is a security risk.

#### Audit:

Follow the below steps and verify that `Open "safe" files after downloading` is Disabled:

1. Click `Safari`.
2. Click `Preferences`.
3. Click `General`.
4. Verify `Open "safe" files after downloading` is unchecked.

To verify the plist follow the below steps:

1. Open the `com.apple.Safari.plist`.
2. Find the token `<key>AutoOpenSafeDownloads</key>`
3. verify this token is immediately followed by `<false/>`

## **Remediation:**

Follow the below steps to set Open "safe" files after downloading to Disabled:

1. Click Safari.
2. Click Preferences.
3. Click General.
4. Uncheck the Open "safe" files after downloading checkbox.

To configure the plist follow the below steps:

1. Open the `com.apple.Safari.plist`.
2. Find the token `<key>AutoOpenSafeDownloads</key>`
3. Ensure this token is immediately followed by `<false/>`

## **Default Value:**

Enabled.

## **CIS Controls:**

### 7 Email and Web Browser Protections

Email and Web Browser Protections

## ***2 Tabs***

This section is intentionally blank and exists to ensure the structure of Safari benchmarks is consistent.

## 3 AutoFill

This section contains settings under the AutoFill tab of the Safari Browser.

### 3.1 (L2) Ensure 'AutoFill web forms: User names and passwords' is 'Disabled' (Scored)

#### Profile Applicability:

- Level 2

#### Description:

Safari can utilize a user-level keychain for credential storage, and then access that information when revisiting websites on the same domain. By disabling this feature the user will be prompted to manually enter their credentials when they visit a website.

#### Rationale:

If this setting is enabled, users can have Safari store and retrieve passwords through a user-level keychain and provide them automatically the next time they visit a site. An intruder who has unrestricted access to your computer can gain access to secure site areas.

#### Audit:

Follow the below steps and verify that `AutoFill web forms: User names and passwords` is Disabled:

1. Click `Safari`.
2. Click `Preferences`.
3. Click `AutoFill`.
4. Verify `AutoFill web forms: User names and passwords` is unchecked.

To verify the plist follow the below steps:

1. Open the `com.apple.Safari.plist`.
2. Find the token `<key>AutoFillPasswords</key>`
3. verify this token is immediately followed by `<false/>`

## Remediation:

Follow the below steps to set AutoFill web forms: User names and passwords to Disabled:

1. Click Safari.
2. Click Preferences.
3. Click AutoFill.
4. Uncheck AutoFill web forms: User names and passwords.

To configure the plist follow the below steps:

1. Open the `com.apple.Safari.plist`.
2. Find the token `<key>AutoFillPasswords</key>`
3. Ensure this token is immediately followed by `<false/>`

## Default Value:

Enabled.

## CIS Controls:

13 Data Protection

Data Protection

## 3.2 (L2) Ensure 'AutoFill web forms: Credit cards' is 'Disabled' (Scored)

### Profile Applicability:

- Level 2

### Description:

Safari can store and retrieve payment card information in the user-level keychain. The information is collected during an online purchase, following the user's permission. It is recommended that Safari be configured to not store payment card information in cases where security is paramount.

### Rationale:

If a user's console session is compromised, credit card information may be auto-filled into a website for a malicious purpose.

### Audit:

Follow the below steps and verify that `AutoFill web forms: Credit cards` is Disabled:

1. Click `Safari`.
2. Click `Preferences`.
3. Click `AutoFill`.
4. Verify `AutoFill web forms: Credit cards` is unchecked.

To verify the plist follow the below steps:

1. Open the `com.apple.Safari.plist`.
2. Find the token `<key>AutoFillCreditCardData</key>`
3. verify this token is immediately followed by `<false/>`

### Remediation:

Follow the below steps to set `AutoFill web forms: Credit cards` to Disabled:

1. Click `Safari`.
2. Click `Preferences`.
3. Click `AutoFill`.
4. Uncheck `AutoFill web forms: Credit cards`.

To configure the plist follow the below steps:

1. Open the `com.apple.Safari.plist`.
2. Find the token `<key>AutoFillCreditCardData</key>`
3. Ensure this token is immediately followed by `<false/>`

**Default Value:**

Enabled.

**CIS Controls:**

13 Data Protection

Data Protection

### 3.3 (L2) Ensure 'AutoFill web forms: Other forms' is 'Disabled' (Scored)

#### Profile Applicability:

- Level 2

#### Description:

Safari can store the information typed in forms for later use on other websites. It is recommended that Safari be configured such that it does not store and auto-fill form contents.

#### Rationale:

If Safari or other applications executing at equal or higher security contexts is compromised, potentially sensitive, persisted, form data is at increased risk.

#### Audit:

Follow the below steps and verify that `AutoFill web forms: Other forms` is Disabled:

1. Click `Safari`.
2. Click `Preferences`.
3. Click `AutoFill`.
4. Verify `AutoFill web forms: Other forms` is unchecked.

To verify the plist follow the below steps:

1. Open the `com.apple.Safari.plist`.
2. Find the token `<key>AutoFillMiscellaneousForms</key>`
3. verify this token is immediately followed by `<false/>`

#### Remediation:

Follow the below steps to set `AutoFill web forms: Other forms` to Disabled:

1. Click `Safari`.
2. Click `Preferences`.
3. Click `AutoFill`.
4. Uncheck `AutoFill web forms: Other forms`.

To configure the plist follow the below steps:



1. Open the `com.apple.Safari.plist`.
2. Find the token `<key>AutoFillMiscellaneousForms</key>`
3. Ensure this token is immediately followed by `<false/>`

**Default Value:**

Enabled.

**CIS Controls:**

13 Data Protection

Data Protection

## 4 Passwords

This section contains settings under the Passwords tab of the Safari Browser.

### 4.1 (L2) Ensure 'AutoFill user names and passwords' is 'Disabled' (Scored)

#### Profile Applicability:

- Level 2

#### Description:

Safari can utilize a user-level keychain for credential storage, and then access that information when revisiting websites on the same domain. By disabling this feature the user will be prompted to manually enter their credentials when they visit a website.

#### Rationale:

If this setting is enabled, users can have Safari store and retrieve passwords through the user-level Keychain and provide them automatically the next time they log in to a site. An intruder who has unrestricted access to your computer for even a minute can gain access to secure site areas.

#### Audit:

Follow the below steps and verify that `AutoFill user names and passwords` is Disabled:

1. Click `Safari`.
2. Click `Preferences`.
3. Click `Passwords`.
4. Verify `AutoFill user names and passwords` is unchecked.

To verify the plist follow the below steps:

1. Open the `com.apple.Safari.plist`.
2. Find the token `<key>AutoFillPasswords</key>`
3. verify this token is immediately followed by `<false/>`

#### Remediation:

Follow the below steps to set `AutoFill user names and passwords` to Disabled:

1. Click `Safari`.

2. Click `Preferences`.
3. Click `Passwords`.
4. Uncheck the `AutoFill user names and passwords` checkbox.

To configure the plist follow the below steps:

1. Open the `com.apple.Safari.plist`.
2. Find the token `<key>AutoFillPasswords</key>`
3. Ensure this token is immediately followed by `<false/>`

**Default Value:**

Enabled.

**CIS Controls:**

13 Data Protection

Data Protection

## ***5 Search***

This section is intentionally blank and exists to ensure the structure of Safari benchmarks is consistent.

## 6 Security

This section contains settings under the Security tab of the Safari Browser.

### 6.1 (L1) Ensure 'Warn when visiting a fraudulent website' is 'Enabled' (Scored)

#### Profile Applicability:

- Level 1

#### Description:

Safari can be configured to alert the user that the site they are visiting is known to be malicious. It is recommended that this capability be enabled.

#### Rationale:

Users will be alerted about known malicious web sites, thus decreasing the probability of a user's browser or system being exploited by known malware or phishing site.

#### Audit:

Follow the below steps and verify that Warn when visiting a fraudulent website is Enabled:

1. Click Safari.
2. Click Preferences.
3. Click Security.
4. Verify Warn when visiting a fraudulent website is checked.

To verify the plist follow the below steps:

1. Open the `com.apple.Safari.plist`.
2. Find the token `<key>WarnAboutFraudulentWebsites</key>`
3. verify this token is immediately followed by `<true/>`

#### Remediation:

Follow the below steps to set Warn when visiting a fraudulent website to Enabled:

1. Click Safari.
2. Click Preferences.

3. Click `AutoFill`.
4. Check the `Warn when visiting a fraudulent website` checkbox.

To configure the plist follow the below steps:

1. Open the `com.apple.Safari.plist`.
2. Find the token `<key>WarnAboutFraudulentWebsites</key>`
3. Ensure this token is immediately followed by `<true/>`

**Default Value:**

Enabled.

**CIS Controls:**

7 Email and Web Browser Protections

Email and Web Browser Protections

## 6.2 (L2) Ensure 'Enable JavaScript' is 'Disabled' (Scored)

### Profile Applicability:

- Level 2

### Description:

JavaScript enables web site authors to create enhanced user interfaces. In support of this, JavaScript enables web sites to programmatically read and alter the document object model (DOM) for the rendered web site as well as instantiate various objects, such as asynchronous XML HTTP request (XHR) objects. It is recommended that JavaScript be disabled.

### Rationale:

JavaScript continues to be an attack vector for exploiting vulnerabilities in the browser. Additionally, JavaScript is commonly leveraged by exploit authors to create a deterministic memory layout in support of increasing the reliability of exploits.

### Audit:

Follow the below steps and verify that `Enable JavaScript` is Disabled:

1. Click `Safari`.
2. Click `Preferences`.
3. Click `Security`.
4. Verify `Enable JavaScript` is unchecked.

To verify the plist follow the below steps:

1. Open the `com.apple.Safari.plist`.
2. Find the token `<key>WebKitJavaScriptEnabled</key>`
3. verify this token is immediately followed by `<false/>`

### Remediation:

Follow the below steps to set `Enable JavaScript` to Disabled:

1. Click `Safari`.
2. Click `Preferences`.
3. Click `AutoFill`.
4. Uncheck the `Enable JavaScript` checkbox.

To configure the plist follow the below steps:

1. Open the `com.apple.Safari.plist`.
2. Find the token `<key>WebKitJavaScriptEnabled</key>`
3. Ensure this token is immediately followed by `<false/>`

**Default Value:**

Enabled.

**CIS Controls:**

**7.3 Limit Use Of Scripting Languages In Browsers And Email Clients**

Limit the use of unnecessary scripting languages in all web browsers and email clients. This includes the use of languages such as ActiveX and JavaScript on systems where it is unnecessary to support such capabilities.



## 6.3 (L2) Ensure 'Block pop-up windows' is 'Enabled' (Scored)

### Profile Applicability:

- Level 2

### Description:

The `Block pop-up windows` feature is used to block pop-up windows which a website might open with or without any user interaction. Pop-ups can be used to open un-trusted malicious content. It is recommended that the `Popup Blocker` be enabled.

### Rationale:

By enabling `Block pop-up windows`, pop-ups will be blocked which will reduce the likelihood of being redirected to a malicious site.

### Audit:

Follow the below steps and verify that `Block pop-up windows` is Enabled:

1. Click `Safari`.
2. Click `Preferences`.
3. Click `Security`.
4. Verify `Block pop-up windows` is checked

To verify the plist follow the below steps:

1. Open the `com.apple.Safari.plist`.
2. Find the token `<key>WebKitJavaScriptCanOpenWindowsAutomatically</key>`
3. verify this token is immediately followed by `<false/>`

### Remediation:

Follow the below steps to set `Block pop-up windows` to Enabled:

1. Click `Safari`.
2. Click `Preferences`.
3. Click `Security`.
4. Check the `Block pop-up windows` checkbox

To configure the plist follow the below steps:

1. Open the `com.apple.Safari.plist`.
2. Find the token `<key>WebKitJavaScriptCanOpenWindowsAutomatically</key>`
3. Ensure this token is immediately followed by `<false/>`

**Default Value:**

Enabled.

**CIS Controls:**

7 Email and Web Browser Protections

Email and Web Browser Protections

## 7 Privacy

This sections contains settings under the Privacy tab of the Safari Browser.

### 7.1 (L1) Ensure 'Cookies and website data' is set to 'Allow from websites I visit' (Scored)

#### Profile Applicability:

- Level 1

#### Description:

This setting `Allow from websites I visit` allows all first-party cookies and blocks all third-party cookies.

#### Rationale:

Blocking third party cookies can help protect a user's privacy by eliminating some tracking cookies.

#### Audit:

Follow the below steps and verify that `Cookies and website data` is set to `Allow from websites I visit`:

1. Click `Safari`.
2. Click `Preferences`.
3. Click `Privacy`.
4. Verify `Cookies and website data` is set to `Allow from websites I visit`.

To verify the plist follow the below steps:

1. Open the `com.apple.Safari.plist`.
2. Find the token `<key>BlockStoragePolicy</key>`
3. verify this token is immediately followed by `<integer>3</integer>`

#### Remediation:

Follow the below steps to set `Cookies and website data` to `Allow from websites I visit`:

1. Click Safari.
2. Click Preferences.
3. Click Privacy.
4. Set Cookies and website data to Allow from websites I visit.

To configure the plist follow the below steps:

1. Open the `com.apple.Safari.plist`.
2. Find the token `<key>BlockStoragePolicy</key>`
3. Ensure this token is immediately followed by `<integer>3</integer>`

**Default Value:**

Allow from websites I visit.

**CIS Controls:**

13 Data Protection

Data Protection

## ***8 Websites***

This section is intentionally blank and exists to ensure the structure of Safari benchmarks is consistent.

## ***9 Extensions***

This section is intentionally blank and exists to ensure the structure of Safari benchmarks is consistent.

## 10 Advanced

This section contains settings under the Advanced tab of the Safari Browser.

### 10.1 (L1) Ensure 'Show full website address' is 'Enabled' (Scored)

#### Profile Applicability:

- Level 1

#### Description:

This setting controls how the URL is displayed. With it enabled, the full path will be shown. With it disabled, only the high-level domain will be displayed.

#### Rationale:

By displaying the full URL, the user is better informed as to where they are browsing on a given site and may even see sensitive parameters that are being passed via URL.

#### Audit:

Follow the below steps and verify that `Show full website address` is set to `Enabled`:

1. Click `Safari`.
2. Click `Preferences`.
3. Click `Advanced`.
4. Verify the `Show full website address` checkbox is checked.

To verify the plist follow the below steps:

1. Open the `com.apple.Safari.plist`.
2. Find the token `<key>ShowFullURLInSmartSearchField</key>`
3. verify this token is immediately followed by `<true/>`

#### Remediation:

Follow the below steps to set `Show full website address` to `Enabled`:

1. Click `Safari`.
2. Click `Preferences`.
3. Click `Advanced`.
4. Check `Show full website address` checkbox.

To configure the plist follow the below steps:

1. Open the `com.apple.Safari.plist`.
2. Find the token `<key>ShowFullURLInSmartSearchField</key>`
3. Ensure this token is immediately followed by `<true/>`

**Default Value:**

Disabled. (Shortens URL)

**CIS Controls:**

7 Email and Web Browser Protections

Email and Web Browser Protections

## 11 Other

This section contains items not located within Safari Preferences.

### 11.1 (L1) Ensure 'Show Status Bar' is not 'Hidden' (Scored)

#### Profile Applicability:

- Level 1

#### Description:

This setting controls whether mousing over a link displays the full URL that the link will follow.

#### Rationale:

Showing the full URL allows users to validate that a link is performing the action it claims, and may prevent users from following malicious links.

#### Audit:

Follow the below steps and verify that `Show Status Bar` is not 'Hidden`:

1. Click `View`.
2. Verify `Hide Status bar` is displayed.

To verify the plist follow the below steps:

1. Open the `com.apple.Safari.plist`.
2. Find the token `<key>ShowOverlayStatusBar<key>`
3. Verify this token is immediately followed by `<true/>`.

#### Remediation:

Follow the below steps to set `Show Status Bar`:

1. Click `View`.
2. Click `Show Status Bar`.

To configure the plist follow the below steps:



1. Open the `com.apple.Safari.plist`.
2. Find the token `<key>ShowOverlayStatusBar<key>`
3. Ensure this token is immediately followed by `<true/>`

**Default Value:**

Hidden.

**CIS Controls:**

7 Email and Web Browser Protections

Email and Web Browser Protections

# Appendix: Summary Table

Control		Set Correctly	
		Yes	No
<b>1</b>	<b>General</b>		
1.1	(L1) Ensure 'Open "safe" files after downloading' is 'Disabled' (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
<b>2</b>	<b>Tabs</b>		
<b>3</b>	<b>AutoFill</b>		
3.1	(L2) Ensure 'AutoFill web forms: User names and passwords' is 'Disabled' (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
3.2	(L2) Ensure 'AutoFill web forms: Credit cards' is 'Disabled' (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
3.3	(L2) Ensure 'AutoFill web forms: Other forms' is 'Disabled' (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
<b>4</b>	<b>Passwords</b>		
4.1	(L2) Ensure 'AutoFill user names and passwords' is 'Disabled' (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
<b>5</b>	<b>Search</b>		
<b>6</b>	<b>Security</b>		
6.1	(L1) Ensure 'Warn when visiting a fraudulent website' is 'Enabled' (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
6.2	(L2) Ensure 'Enable JavaScript' is 'Disabled' (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
6.3	(L2) Ensure 'Block pop-up windows' is 'Enabled' (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
<b>7</b>	<b>Privacy</b>		
7.1	(L1) Ensure 'Cookies and website data' is set to 'Allow from websites I visit' (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
<b>8</b>	<b>Websites</b>		
<b>9</b>	<b>Extensions</b>		
<b>10</b>	<b>Advanced</b>		
10.1	(L1) Ensure 'Show full website address' is 'Enabled' (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
<b>11</b>	<b>Other</b>		
11.1	(L1) Ensure 'Show Status Bar' is not 'Hidden' (Scored)	<input type="checkbox"/>	<input type="checkbox"/>

# Appendix: Change History

Date	Version	Changes for this version
11/28/17	2.0.0	Rewrite from Original